








AREAS OF APPLICATION

-  General indoor illumination
-  Decorative lighting ,Corridors
-  Back lighting

PRODUCT BENEFITS

-  Highest quality components and premium packaged 5050 LEDs
-  Easy mounting on many smooth surfaces thanks to self-adhesive tape at the back
-  High-performance silicone for extremely long life and flexibility
-  Direct connection to AC power supply thanks to integrated control gear
-  SMD5050, Single Row led strip light with Push-inconnectors enable automatic wiring

PRODUCT FEATURES

-  Type of protection: IP20
-  Material:Silicon
-  Type of LED:SMD 5050,60LED/m

TECHNICAL DATA

Electrical data

Rated power	14.4W/m
Operating voltage	DC 24V
Operating frequency	-
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	1320lm/m
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	5000mm
Width	12mm

Temperature & operating conditions

Ambient Temperature	-15°~ +60°
---------------------	------------

General information

Colour consistency	≤ 3 SDCM
LED type	LED SMD
Lifespan	25,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
5050-60P-12mm	92lm/W	14.4W/m	20	NO

TECHNICAL DRAWING

