



AREAS OF APPLICATION

- Domestic and Commercial Lighting
- Warehouses and other storage areas
- Parking lots, Hotels & similar environment

PRODUCT BENEFITS

- The polycarbonate body and opal diffuser provide high impact resistance
- Uniform, wide-beam light distribution
- The internal aluminum core deals with the heat from the LED chips and assures a long lifespan
- Economical, compact waterproof luminaire designed for use in demanding environments
- High quality LED driver, flicker free driver and Rust-free and flexible mounting clamps

PRODUCT FEATURES

- Type of Protection: IP65 and IK08
- No Lead or Mercury content.
- Energy efficiency class: A+
- Quick and easy installation.

TECHNICAL DATA

Electrical data

Rated power	39W
Operating voltage	AC 220-250V
Operating frequency	50~60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	3900lm
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	1200mm
Width	90mm

Temperature & operating conditions

Ambient Temperature	-20° ~ +50°C
---------------------	--------------

General information

Mounting type	Surface
LED type	SMD LED
Lifespan	50,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-06A-12	100lm/W	39W	65	NO

TECHNICAL DRAWING

