













AREAS OF APPLICATION

-  Landscape Area
-  Wallwashing of building facades
-  General Outdoor Lighting

PRODUCT BENEFITS

-  Even, brilliant lighting effects due to extra narrow, asymmetric or wide optics
-  Simple and Constant current driver with PWM gray control installed inside.
-  Adopt American CREE original LED light source & high Lumen output
-  Aluminum Alloy Material and Suitable for use in areas with Garden and Outdoor Pathway

PRODUCT FEATURES

-  Type of protection: IP66
-  3 Years Warranty.
-  Colour Rendering index R:80

TECHNICAL DATA

Electrical data

Rated power	36W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	2340LM
Color rendering index Ra	80

Light Technical Data

Beam angle	10 X 60°
------------	----------

Dimensions

Length	1000mm
Width	50mm

Temperature & operating conditions

Ambient Temperature	-25~+ 50° C
---------------------	-------------

General information

Mounting type	Surface
LED type	CREE LED
Lifespan	30,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 1301A-36	65lm/W	36W	66	No

TECHNICAL DRAWING

