













AREAS OF APPLICATION

-  Landscape Area
-  Bridge lighting, building facades
-  General area flood lights

PRODUCT BENEFITS

-  Even, brilliant lighting effects due to extra narrow, asymmetric or wide optics
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover
-  Adopt American CREE original LED light source & high Lumen output
-  Extruded Aluminum housing with die-cast aluminum end cap suitable for use in Outdoor areas

PRODUCT FEATURES

-  Type of protection, back side: IP66
-  3 Years Warranty.
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	42W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	2730LM
Color rendering index Ra	80

Light Technical Data

Beam angle	20°,30°,60°,90°
------------	-----------------

Dimensions

Length	1000mm
Width	118mm

Temperature & operating conditions

Ambient Temperature	-25°...+50°
---------------------	-------------

General information

Mounting type	Surface
LED type	CREE SMD LED
Lifespan	30,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 1305A-36	65lm/W	42W	66	NO

TECHNICAL DRAWING

