














## AREAS OF APPLICATION

-  Residential and Commercial
-  Windows, balcony and Corridor
-  Decorative Lighting

## PRODUCT BENEFITS

-  Light body adpots die-casting aluminum, surface with electrostatic plastic coating.
-  Easy installation ways meet the various occasions demands for outdoor projects.
-  Good glare reduction and Low maintenance and operation costs
-  High efficiency and reliability
-  Surface mounted luminaire for outdoor installation on window sill, with symmetric window-washer light distribution

## PRODUCT FEATURES

-  Protection:IP65 and IK10
-  3 Years Warranty.
-  RAL9023 Pearl dark grey or customized

## TECHNICAL DATA

### Electrical data

Rated power	5W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

### Photometrical data

Color temperature	2700-6500K
Luminous flux	350lm
Color rendering index Ra	80

### Light Technical Data

Beam angle	2*120°
------------	--------

### Dimensions

Length(mm)	110
Height	70

### Temperature & operating conditions

Ambient Temperature	-25~+50C°
---------------------	-----------

### General information

Mounting type	Surface
LED type	LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 3220A-3	70lm/W	5W	65	NO

🔍 TECHNICAL DRAWING

