











## AREAS OF APPLICATION

-  Landscape Area
-  Wallwashing of building facades
-  General Outdoor Lighting

## PRODUCT BENEFITS

-  Even, brilliant lighting effects due to extra narrow, asymmetric or wide optics
-  Simple and Constant current driver with PWM gray control installed inside.
-  OSRAM Brand CREE original LED light source & high Lumen output
-  Aluminum Alloy Material and Suitable for use in areas with Garden and Outdoor Pathway

## PRODUCT FEATURES

-  Type of protection: IP65
-  3 Years Warranty.
-  RGB Control

## TECHNICAL DATA

### Electrical data

Rated power	10W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

### Photometrical data

Color temperature	RGB
Luminous flux	500lm
Color rendering index Ra	-

### Light Technical Data

Beam angle	120°
------------	------

### Dimensions

Length	1000mm
Width	49mm

### Temperature & operating conditions

Ambient Temperature	-25~+ 50° C
---------------------	-------------

### General information

Mounting type	Surface
LED type	CREE LED
Lifespan	30,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE/CONTROL
CLX 3317L-48	50lm/W	10W	66	RGBW

**TECHNICAL DRAWING**

