









AREAS OF APPLICATION

-  Facade Lighting
-  Waterfall and Fountain
-  Underwater lighting for swimming pools

PRODUCT BENEFITS

-  Highly efficient COB LED chip and high IP rating on luminaire front side.
-  Use optical PMMA secondary light distribution technology, viewing angle light gathering effects can be adjust
-  Quality and reliability in line with all Structural waterproof technology
-  High strength toughened glass with anti-glare design to have glare free effect
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover

PRODUCT FEATURES

-  IP68 protection and IK10 impact resistant
-  High Quality CREE LED Chip
-  Material:Aluminium body+stainless steel 304 Trim+Tempered glass

TECHNICAL DATA

Electrical data

Rated power	16W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	1200lm
Color rendering index Ra	80

Light Technical Data

Beam angle	45°
------------	-----

Dimensions

Inner Diameter	Ø143mm
Height	87

Temperature & operating conditions

Ambient Temperature	-25~+ 50°C
---------------------	------------

General information

Mounting type	Recessed
LED type	CREE LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX5119B-9	75lm/W	16W	68	NO

TECHNICAL DRAWING

