






AREAS OF APPLICATION

-  General illumination
-  Living Room, offices, conference rooms
-  Retail, Shopping Mall and Hospital

PRODUCT BENEFITS

-  Suitable for use in areas with low ceilings thanks to compact design
-  Affordable solution for retrofit or new installations
-  Elegant design with Anti-glare lens and exclusive design
-  Creates a gentle, natural light, ensuring visual comfort
-  Integrated PMMA front material and aluminum housing for good heat dissipation

PRODUCT FEATURES

-  Type of protection: IP20
-  Color Rendering index:80
-  Aluminium Alloy Housing & Frosted PMMA Lens

TECHNICAL DATA

Electrical data

Rated power	6.5W
Operating voltage	AC100-250V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	485±5%lm
Color rendering index Ra	80

Light Technical Data

Beam angle	100°
------------	------

Dimensions

Inner Diameter	Ø94mm
Height	75mm

Temperature & operating conditions

Ambient Temperature	-15°~ +60°
---------------------	------------

General information

Mounting type	Ceiling Recessed
LED type	LED
Lifespan	35,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXG3-6.5W	75lm/W	6.5W	20	NO

TECHNICAL DRAWING

