















AREAS OF APPLICATION

-  Warehouses and logistic halls
-  General lighting for high ceilings
-  Production facilities

PRODUCT BENEFITS

-  Unique heat sink design with air channels to increase system reliability
-  The system is suitable for both new builds and retrofit installations
-  Super slim design and suits for hook
-  Massive aluminium die - cast heat sink with notably good heat dissipation abilities
-  Different luminous flux and beam angles for different mounting heights available

PRODUCT FEATURES

-  Durable and compact low-profile housing design
-  IP65 grade protection
-  5 Years warranty
-  Energy efficiency class A+ & A++

TECHNICAL DATA

Electrical data

Rated power	200 W
Operating voltage	AC100~277V
Operating frequency	50~60Hz
Power factor	>0.95

Photometrical data

Color temperature	2700K - 6500K
Luminous flux (lm)	28000±2000
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Height (mm)	190
Diameter (mm)	360

Temperature & operating conditions

Ambient Temperature	-30~+55°C
---------------------	-----------

General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	50000 hours



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXHB 09-200 W	140±10lm/W	200 W	65	YES

TECHNICAL DRAWING

