



AREAS OF APPLICATION

- Reception areas, Foyers, Elevators
- Halls, Kitchen, conference rooms
- Direct replacement for luminaires with fluorescent lamps

PRODUCT BENEFITS

- Low flicker light thanks to special electronic control gear
- High Lumen efficiency and slim design with height of only 8mm
- Polystyrene diffuser with aluminum housing for improved heat dissipation
- Suspension and Surface Mount are possible with accessories
- Excellent diffused beam shape from a range of optics

PRODUCT FEATURES

- Type of protection: IP20
- Long lifetime: up to 50,000 h.
- Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	60W
Operating voltage	AC190-250V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	5100lm
Color rendering index Ra	80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length & Width	595x595mm
Height	8mm

Temperature & operating conditions

Ambient Temperature	-15° ~ +50°
---------------------	-------------

General information

Mounting type	Ceiling Recessed
LED type	SMD LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
LK0606	85	60W	20	NO

TECHNICAL DRAWING

