














AREAS OF APPLICATION

-  General illumination
-  Living Room, offices, conference rooms
-  Retail, Shopping Mall and Hospital

PRODUCT BENEFITS

-  Suitable for use in areas with low ceilings thanks to compact design
-  Affordable solution for retrofit or new installations
-  Elegant design with Anti-glare lens and exclusive design
-  Creates a gentle, natural light, ensuring visual comfort
-  Integrated PMMA front material and aluminum housing for good heat dissipation

PRODUCT FEATURES

-  Type of protection: IP20
-  Color Rendering index:80
-  Aluminium Alloy Housing & Frosted PMMA Lens

Recessed Up Mounting Type.

Long lifetime: up to 35,000 h.

TECHNICAL DATA

Electrical data

Rated power	7W
Operating voltage	AC170-265V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	560±5%lm
Color rendering index Ra	80

Light Technical Data

Beam angle	38°
------------	-----

Dimensions

Cutout Diameter	Ø78mm
Height	75mm

Temperature & operating conditions

Ambient Temperature	-15°~ +60°
---------------------	------------

General information

Mounting type	Ceiling Recessed
LED type	LED
Lifespan	35,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXQ382A	80lm/W	7W	20	NO

TECHNICAL DRAWING

