











AREAS OF APPLICATION

-  Facade Lighting
-  Ambient Outdoor wall lighting
-  Buildings

PRODUCT BENEFITS

-  Highly efficient American CREE LED chip and high IP rating.
-  Slim and robust housing - constructed from durable die cast aluminium.
-  Ruggedly constructed surface mount fixture for outdoor applications
-  Guarantee a high level of weather and UV ray resistance.

PRODUCT FEATURES

-  IP66 protection & IK07
-  High quality CREE LED Chip.
-  Material: Aluminium body + Stainless Steel + Tempered glass.

TECHNICAL DATA

Electrical data

Rated power	150W
Operating voltage	AC100-240V
Operating frequency	50-60Hz
Power factor	0.90

Photometrical data

Color temperature	2700K
Luminous flux(lm)	15000lm
Color rendering index Ra	80

Light Technical Data

Beam angle	5°, 20°
------------	---------

Dimensions

Width (mm)	300mm
Height (mm)	170mm

temperature & operating conditions

Ambient Temperature	-30°C~+50°C
---------------------	-------------

General information

Mounting type	Surface
LED type	CREE LED
Lifespan	50,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-SL1310EE-12	100lm/W	150W	66	NO

● TECHNICAL DRAWING

