









## AREAS OF APPLICATION

-  Traffic tunnels
-  Underpasses

## PRODUCT BENEFITS

-  It has the high level of visual comfort, With milky cover and wide beam angle light distribution.
-  It provides excellent lighting uniformity on the road and walls and increases visual comfort and safety.
-  With 130lm/w high efficiency output, CLX tunnel light can help you to save more energy and cost.

## PRODUCT FEATURES

-  IP65 and IK10 Grade protection
-  Excellent lighting uniformity on the road and walls
-  5 Years warranty
-  Soft light increases visual comfort and safety
-  Energy efficiency class A+&A++

## TECHNICAL DATA

### Electrical data

Rated power	180 W
Operating voltage	AC100~277V
Operating frequency	47~63Hz
Power factor	>0.95

### Photometrical data

Color temperature	2700 - 6500K
Luminous flux (lm)	23400 ± 1800
Color rendering index Ra	>80

### Light Technical Data

Beam angle	120°
------------	------

### Dimensions

Length (mm)	861.0
Width (mm)	140.0

### Temperature & operating conditions

Ambient Temperature	-30~+55°C
---------------------	-----------

### General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	50000 hours



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXT16-180 W	130±10	180 W	65	YES

**TECHNICAL DRAWING**

