



## AREAS OF APPLICATION

- Traffic tunnels
- 😳 Other outdoor lighting

## PRODUCT BENEFITS

- 😨 Its robust aluminum housing and high quality Tomcarline power driver provides excellent heat dissipation and longer life time with different beam angle lens.
- With LM80 EMC3030 LED chips, its whole system light effeciency can reach 130lm/w, which can help customers to save more energy.
- PHigh quality Tomcarline driver ensure longer lifetime

# PRODUCT FEATURES

- PIP65 Grade protection
- PRobust design with outstanding heat management
- 5 Years warranty
- Different beam angles for options
- Finergy efficiency class A+&A++

# TECHNICAL DATA

#### O Electrical data

Rated power	120 W AC100~277V 47~63Hz	
Operating voltage		
Operating frequency		
Power factor	>0.9	

## O Photometrical data

Color temperature	2500K - 6500K	
Luminous flux (lm)	15600 ± 1200	
Color rendering index Ra	>70	

### O Light Technical Data

Beam angle	120°

#### **O** Dimensions

Length (mm)	172.0		
Width (mm)	263.0		

### • Temperature & operating conditions

Ambient Temperature	-30~+50°C

#### • General information

Mounting type Surface mou		
LED type	SMD LED	
Lifespan	50000 hours	

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX T36C-120W	130 ±10	120 W	65	YES

# TECHNICAL DRAWING







