















AREAS OF APPLICATION

-  Parking Facilities, Corridors and halls
-  Warehouses and other storage areas
-  Factories and production areas.

PRODUCT BENEFITS

-  The massive internal aluminum housing provides excellent heat dissipation.
-  Its polycarbonate housing is cast from a single mold
-  The internal aluminum core deals with the heat from the LED chips and assures a long lifespan
-  Slim design, ideal for space-constrained industrial applications
-  The LED Tri-Proof Lights uses powerful SMD2835 Chip sets for achieving the highest efficiency in lighting

PRODUCT FEATURES

-  IP69K and IK10 under all conditions
-  5 Years Warranty.
-  Energy efficiency class:A+
-  No UV or IR and completely mercury free

TECHNICAL DATA

Electrical data

Rated power	75W
Operating voltage	AC100-277V
Operating frequency	50~60Hz
Power factor	0.90

Photometrical data

Color temperature	2700-6500K
Luminous flux	9700±400lm
Color rendering index Ra	>80

Light Technical Data

Beam angle	120°
------------	------

Dimensions

Length	1470mm
Width	78mm

Temperature & operating conditions

Ambient Temperature	-30°~ +50°C
---------------------	-------------

General information

Mounting type	Surface
LED type	SMD LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLXT56-75W15	130±5lm/W	75W	69K	YES

TECHNICAL DRAWING

