



## AREAS OF APPLICATION

- Parking lots & Streets
- Outdoor basketball court, tennis court.
- Walkways and building grounds.

## PRODUCT BENEFITS

- Aluminum PCB's containing 1W 3030 chip with Excellent Light Distribution
- Highly transparent lenses available with several different beam angles and with industrial great cooling paste to assure a perfect connection between the PCBs
- Excellent heat dissipation & modern design.
- Professional optical design: best use of light to the target area while not creating glare to driver and environment

## PRODUCT FEATURES

- Each module can be replaced to minimize maintenance costs
- Streamlined modern design
- 5 Years warranty

## TECHNICAL DATA

### Electrical data

Rated power	200 W
Operating voltage	AC100~277V
Operating frequency	50~60Hz
Power factor	>0.9

### Photometrical data

Color temperature	2700-6500K
Luminous flux (lm)	28000±1000
Color rendering index Ra	>80

### Light Technical Data

Beam angle	TYPE 5
------------	--------

### Dimensions

Length (mm)	580
Width (mm)	310

### Temperature & operating conditions

Ambient Temperature	-20~+65°C
---------------------	-----------

### General information

Mounting type	Surface mounted
LED type	SMD LED
Lifespan	5 Years



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX T60C-200W	140±5 lm/W	200 W	66	YES

**TECHNICAL DRAWING**

