














## AREAS OF APPLICATION

-  Facade Lighting
-  Ambient uplighting in gardens
-  Outdoor pathways

## PRODUCT BENEFITS

-  Highly efficient COB LED chip and high IP rating on luminaire front side.
-  Slim and robust housing - constructed from durable die cast aluminium
-  Ruggedly constructed in-ground fixture for outdoor applications
-  High strength toughened glass with anti-glare design to have glare free effect
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover

## PRODUCT FEATURES

-  IP67 protection and IK09 impact resistant
-  High Quality CREE LED Chip
-  Material: Aluminium body + stainless steel 304 Trim + Tempered glass

## TECHNICAL DATA

### Electrical data

Rated power	12W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

### Photometrical data

Color temperature	2700-6500K
Luminous flux	1080lm
Color rendering index Ra	80

### Light Technical Data

Beam angle	45°
------------	-----

### Dimensions

Inner Diameter	Ø156mm
Height	90

### Temperature & operating conditions

Ambient Temperature	-25~+ 50°C
---------------------	------------

### General information

Mounting type	Recessed
LED type	CREE LED
Lifespan	50,000h



SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-UDG00-RD12	90lm/W	12W	67	NO

**TECHNICAL DRAWING**

