













AREAS OF APPLICATION

-  Landscape Area
-  Bridge lighting, building facades
-  General Outdoor Lighting

PRODUCT BENEFITS

-  Even, brilliant lighting effects due to extra narrow, asymmetric or wide optics
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover
-  Adopt American CREE original LED light source & High Lumen output
-  Extruded Aluminium housing with die-cast aluminium end cap suitable for use in outdoor areas

PRODUCT FEATURES

-  Type of protection, back side : IP66
-  3 Years Warranty
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	36W
Operating voltage	AC100-240V
Operating frequency	50/60Hz
Power factor	0.90

Photometrical data

Color temperature	GREEN
Luminous flux(lm)	3600lm
Color rendering index Ra	80

Light Technical Data

Beam angle	20°,30°,60°,90°
------------	-----------------

Dimensions

Length(mm)	1000mm
Width(mm)	118mm

temperature & operating conditions

Ambient Temperature	-25°C~+50°C
---------------------	-------------

General information

Mounting type	Surface
LED type	CREE SMD LED
Lifespan	30,000h

SPECIFICATION

MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX 1305A-24	100lm/W	36W	66	NO

● TECHNICAL DRAWING

