



## AREAS OF APPLICATION

- 💡 Outdoor lighting for Buildings
- 💡 Decoration/Room/Tunnel/Other

## PRODUCT BENEFITS

- 💡 High quality LED provides long lifespan
- 💡 Designed for extreme weather conditions
- 💡 Grey, Black, white and custom colour options are available
- 💡 Surface mount bracket and optional spike available
- 💡 High quality LED driver, flicker free driver and Rust-free and flexible mounting clamps

## PRODUCT FEATURES

- 💡 Type of Protection: IP66
- 💡 Energy Efficient
- 💡 RGB/RGBW 5 Years, Single CCT 5 Years
- 💡 On/Off DMX 512 Controlling

## TECHNICAL DATA

### ● Electrical data

Rated power	12W
Operating voltage	DC24V
Operating frequency	-
Power factor	-

### ● Photometrical data

Color temperature	2700-6500K
Luminous flux(lm)	300lm (RGB/RGBW), 720lm(4000K)
Color rendering index Ra	>80

### ● Light Technical Data

Beam angle	120°
------------	------

### ● Dimensions

Length(mm)	995mm
Width(mm)	23mm
Height(mm)	44mm

### ● temperature & operating conditions

Ambient Temperature	-40°~+60°C
---------------------	------------

### ● General information

Mounting type	Surface
LED type	SMD LED
Lifespan	20,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
WN-LNWW18	RGB/RGBW,25lm/W 4000K,80lm/W	12W	66	NO

● TECHNICAL DRAWING

