














AREAS OF APPLICATION

-  Landscape Area
-  Outdoor Pathway
-  Garden, Facade Lighting

PRODUCT BENEFITS

-  Matching colour temperature and finish to the Architectural exterior range
-  Die-cast aluminium construction with Clear Tempered Glass Diffuser.
-  Good glare reduction and low maintenance and operation costs
-  Suitable for use in areas with Garden and Outdoor Pathways
-  Excellent diffused beam shape from a range of optics

PRODUCT FEATURES

-  Type of protection IP66, Class I
-  Lifespan up to 15000h
-  Colour Rendering Index R:80

TECHNICAL DATA

Electrical data

Rated power	13W
Operating voltage	AC 100-264V
Operating frequency	50-60Hz
Power factor	>0.90

Photometrical data

Color temperature	2200K
Luminous flux(lm)	1300lm
Color rendering index Ra	≥80

Light Technical Data

Beam angle	45°
------------	-----

Dimensions

Diameter (mm)	Ø75mm
Height (mm)	369mm

temperature & operating conditions

Ambient Temperature	-25°C...+50°C
---------------------	---------------

General information

Mounting type	Spike/Clamp Mounted
LED type	CREE LED
Lifespan	15,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX-SL1145UE-1	100lm/W	13W	66	NO

● TECHNICAL DRAWING

