














AREAS OF APPLICATION

-  Facade Lighting
-  Ambient uplighting in gardens
-  Outdoor pathway

PRODUCT BENEFITS

-  Highly efficient CREE LED chip and high IP rating on luminaire front side
-  Slim and robust housing - constructed from durable die cast aluminium + SS316
-  Ruggedly constructed in-ground fixture for outdoor applications
-  High strength toughened glass with anti-glare design to have glare free effect
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover

PRODUCT FEATURES

-  IP 67 protection
-  High quality CREE COB LED Chip.
-  Material: Aluminium body + Stainless Steel + Tempered glass.

TECHNICAL DATA

Electrical data

Rated power	10W
Operating voltage	DC24V
Operating frequency	-
Power factor	0.90

Photometrical data

Color temperature	RGBW 4 in 1
Luminous flux(lm)	300lm
Color rendering index Ra	80

Light Technical Data

Beam angle	20°
------------	-----

Dimensions

Diameter (mm)	Ø135mm
Height (mm)	139mm

temperature & operating conditions

Ambient Temperature	-25°C~+50°C
---------------------	-------------

General information

Mounting type	Recessed
LED type	CREE LED
Lifespan	25,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX- SL2161CF-1	30lm/W	10W	67	NO

● TECHNICAL DRAWING

