














AREAS OF APPLICATION

-  Facade Lighting
-  Ambient uplighting in gardens
-  Outdoor pathway

PRODUCT BENEFITS

-  Highly efficient CREE LED chip and high IP rating on luminaire front side
-  Slim and robust housing - constructed from durable die cast aluminium + SS316
-  Ruggedly constructed in-ground fixture for outdoor applications
-  High strength toughened glass with anti-glare design to have glare free effect
-  High quality lens made of polycarbonate, secondary optics with tempered glass cover

PRODUCT FEATURES

-  IP 67 protection
-  High quality CREE LED Chip.
-  Material: Aluminium body + Stainless Steel + Tempered glass.

TECHNICAL DATA

Electrical data

Rated power	20W
Operating voltage	AC100-240V
Operating frequency	50-60Hz
Power factor	>0.90

Photometrical data

Color temperature	2200K
Luminous flux(lm)	2000lm
Color rendering index Ra	≥80

Light Technical Data

Beam angle	20°
------------	-----

Dimensions

Diameter (mm)	Ø185mm
Height (mm)	188mm

temperature & operating conditions

Ambient Temperature	-25°C~+50°C
---------------------	-------------

General information

Mounting type	Recessed
LED type	CREE LED
Lifespan	25,000h

SPECIFICATION				
MODEL	LUMINOUS EFFICIENCY	POWER	IP RATING	DIMMABLE
CLX- SL2162CE-2	100lm/W	20W	67	NO

● TECHNICAL DRAWING

